REPORT DO	CUMENTATION PAGE		mp 00	
Public reporting burden for this collection of informati gathering and maintaining the data needed, and comprollection of information, including suggestions for re Davis Highway, Suite 1204, Arlington, VA 22202-43 1. AGENCY USE ONLY (Leave blank)		ormation	BL-TR-00- 17J	a sources, ect of this Jefferson 3.
1. AGENCY USE ONLY (Leave blank)	June 2000	J. I.	07/01/94 - 09/30/98	
4. TITLE AND SUBTITLE UNSTEADY HEAT TRANSFER OF WRIGHT LABS	·*·	CH FACILITY AT	5. FUNDING NUMBERS F49620-94-1-0269	
6. AUTHOR(S) John E. LaGraff				
7. PERFORMING ORGANIZATION NAM DEPARTMENT OF MECHANICAL ENGINEERING Syracuse University Syracuse, New York 13244		NUFACTURING	8. PERFORMING ORGA REPORT NUMBER	NIZATION
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AIR FORCE OFFICE OF SCIENTIFIC RESEARCH 801 N. Randolph St. Arlington VA 22203			10. SPONSORING/MONITORING AGENCY REPORT NUMBER AFOSR	
11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION AVAILABILITY STA	TEMENT		12b. DISTRIBUTION CO	DE
UNLIMITED				
13. ABSTRACT (Maximum 200 words) Steady-state and time resolved heat to turbine. The tests were conducted in Laboratories in Dayton, Ohio. The hoxford University Osney Turbomach in addition to the present test blade a data, and other techniques to measure technical results have been reported in the control of the contro	the blow-down (transient) To eat transfer instrumentation valuary Laboratory. Tests wer flowing comparisons to be made heat transfer. Ultimately, of	urbine Research Fac was designed, fabric te conducted in the T lade with steady and	ility (TRF) at the USAF atted, and installed on the RF with an array of instrunsteady measurements,	Wright test vane at the rumental blades aerodynamic
		200	00929 0	43
14. SUBJECT TERMS UNSTEADY HEAT TRANSFER O LABS.	N THE TURBINE RESEAR	CH FACILITY AT	WRIGHT 15. NUMBER O	
	SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASS OF ABSTRACT	IFICATION 20. LIMITATIO	N OF ABSTRAC

Standard Form 298 (Rev. 2-89) (EG) Prescribed by ANSI Std. 239.18 Designed using Perform Pro, WHS/DIOR, Oct 94

UU

Final Report Account F49620-94-1-0269

U.S. Air Force Office of Scientific Research AASERT Supplement Grant

[Parent Proposal USAFOSR F49620-92-J-0079 Turbulent Spot Generation and Growth Rates in a Compressible Boundary Layer]

Title of AASERT Grant: Unsteady Heat Transfer on the Turbine

Research Facility at Wright Labs

Dates: of AASERT Grant: 1 July 1994 – 30 September 1998

Amount of Grant: \$121,139

Principal Investigator: John E. LaGraff

Department of Mechanical, Aerospace, and

Manufacturing Engineering

Syracuse University

Syracuse, New York 13244

(315) 443-1189

Abstract

Steady-state and time resolved heat transfer rates were measured on a first stage vane of a modern high pressure aircraft turbine. The tests were conducted in the blowdown (transient) Turbine Research Facility (TRF) at the USAF Wright Laboratories in Dayton, Ohio. The heat transfer instrumentation was designed, fabricated, and installed on the test vane at the Oxford University Osney Turbomachinary Laboratory. Tests were conducted in the TRF with an array of instrumental blades in addition to the present test blade allowing comparisons to be made with steady and unsteady measurements, aerodynamic data, and other techniques to measure heat transfer. Ultimately, comparisons with prediction techniques were made. Full technical results have been reported in the literature (Refs. 1, 2).

Introduction

The AASERT Program was designed as a supplemental grant to an existing USAFOSR grant that would support an additional graduate student to conduct a specific research project closely related to the original grant. The funding was to cover only the cost of supporting this student. The parent proposal included developing a new type of sputtered thin film gauge to be used in the detection and tracking of high-frequency unsteadiness associated with transitional boundary layers. These thin film gauges had the ability to measure absolute surface heat transfer levels on complex surfaces at wide bandwidths. The AASERT proposal made by the principal investigator was to instrument a real vane on a stage of a modern high-pressure turbine being proposed for testing in the recently commissioned Turbine Research Facility (TRF) at Wright Laboratories.

The AASERT Student spent two periods of residence at Oxford to learn the new techniques and oversee the instrumentation of the vane. He also spent an extended period of time at Wright Labs to learn the operation of the TRF and relevant instrumentation and data acquisition systems. He also, of course, completed his residency requirements for the Syracuse University M.S. degree and successfully defended his thesis in June 1997.

Results

Full technical results of this project are described in the M.S. thesis of Christopher Joe, the AASERT student supported by this grant (Ref. 1). A technical paper was also produced which relates this work to other measurements and predictions conducted for the TRF project (Ref. 2).

Student Supported

Christopher Joe - BSAE 1995, Syracuse University

MSAE 1997, Syracuse University

Thesis Title: Unsteady Heat Transfer on the Turbine Research

Facility at Wright Laboratory

Transitions to Industry

The supported student, Christopher Joe, was offered a job by Pratt & Whitney Engine Company before he had finished his thesis. The company, whose engine was being tested as part of the test in the TRF, was interested in the experimental technique and knowledge of the subject of turbine heat transfer that Christopher had developed and subsequently offered him a position with their company. The technical publication (Ref. 2) including this research was published as part of the findings of a larger Pratt & Whitney/USAF program.

References

- 1 Joe, C. R., "Unsteady Heat Transfer on the Turbine Research Facility at Wright Laboratory," M.S. Thesis, Syracuse University, 1997.
- 2 Joe, C. R., Montesdeoca, X.A., Soechting, F. O., MacArthur, C. D., and Meininger, M., "High Pressure Turbine Vane Annular Cascade Heat Flux and Aerodynamic Measurements with Comparison to Predictions," ASME Paper 98-GT-430, 1998.